

Contemporary Styling... Providence & Tiburon...

A signature style has always defined Thelin Stoves and this characteristic is strongly stated in the Providence and Tiburon. Customizing is accomplished through a choice of louver panel inserts and surround choices. Equipped with all standard Thelin Pellet Features, the Tiburon and Providence offer simplified service with removable panels and slide out cabinets. Flue cleaning access and ash removal is also simplified. Additionally, the Providence may be built into new and remodel construction without a fireplace! **Awarded Two Hearth & Home Vista Awards for Design and Operation Features the Tiburon and Providence are the Premium Product Choice!**



Providence Features:

- Easy access cleaning ports
- Quick disconnect flue outlet
- Vacuum assist clean function
- Washable convection air filter
- Advanced heat exchanger
- Adjustable hopper
- Built-in wall option



Tiburon Features:

- Designer Grills
- Color Panel & Lid
- Easy access cleaning
- Advanced heat exchanger

Performance and Specifications

Btu/Hour range:	0 - 45,800	Width:	26.4"
Hopper capacity:	Adj. @26"= 52lbs., 22"= 38lbs.	Depth:	16"
Fuel:	Wood Pellets	Weight:	200 lbs.
Outside Air Size:	3"	Electrical:	35 Watts
Height:	Adj. 22" - 26"	Venting:	4" Std., 3" Opt'l



Performance and Specifications

Btu/Hour range:	0 - 44,500	Width:	16.5"
Hopper capacity:	51 lbs.	Depth:	26.2"
Fuel:	Wood Pellets	Weight:	215 lbs.
Outside Air Size:	3"	Electrical:	35 Watts
Height:	40.25"	Venting:	3" Type "PL"



Appearances or features from those depicted in this brochure. Refer to the Owner's Manual for complete installation instructions. Installation must conform with local building codes.

No Fireplace? No Problem!

You can still enjoy the looks and warmth of the Providence even if you do not have a fireplace - The Providence is approved for use in wood frame construction so that you can add your own mantel and stone facing to look just like a site built fireplace!



Thelin Company Limited Warranty

All Thelin Stoves are warranted from defect in workmanship for five years. Control systems, electrical, and plated components are warranted for one year. See specific product warranty for details.



63 Laxalt Dr. • Carson City, NV 89706
(775) 241-2586

www.thelinco.com

Distributed By



P/N 00.0075.0114 • 01/15



Where comfort begins



Theelin Company - Continues the rich tradition of craftsmanship established over 35 years ago when the company was founded. Thelin Stoves and heaters are attractive and functional and have been recognized worldwide for innovative design. Classic Series now available in three categories, wood pellet burning, gas, and cord wood. Contemporary Series available in wood pellet freestanding and fireplace insert.

Parlour & Gnome Pellet Heaters

Classic styling and new technology combined to offer push button operating ease. Thelin pellet heaters offer three heat ranges with Auto Ignition (only with AC power) and thermostat operation make this a remarkable heater. Battery back up ready, consider adding the optional 12VDC battery for true back up heat. Parlour and Gnome models represent large and small space heating choices with a burn rate range of 40,000 and 27,000 btu. Environmentally conscience with a Ultra Low EPA emissions output of only 1.2 grams per hour for the Gnome and .43 grams per hour for the Parlour. With convenience, durability and vintage styling in mind, this unique stove will add a touch of elegance to your home.



SPECIFICATIONS	PARLOUR	GNOME	PERFORMANCE	PARLOUR	GNOME
Height	43"	34"	Feed Rate	5 lbs. per. Hr. (High) 1.5 lbs. per. Hr. (Low)	Low 1 lb. per hour
Weight	180 lbs.	145 lbs.	Combustion Efficiency	93.34% - 40,000 BTU pr Hr.	94% - 27,000 BTU pr Hr.
Diameter	20"	17.5"	Heat Exchange Efficiency	72.19% - 31,500 BTU pr Hr.	69% - 18,000 BTU
Door Opening	14" x 9.5"	8" x 10"	Heating Capacity	1500 - 2000 sq. ft.*	500 - 850 sq. ft.*
Exhaust Vent	3"	3"	Power Consumption	27 watts - (.25 amps - 110V / 2.25 amps -12V mode)	27 watts
Exhaust to floor	12.25"	11.25"	Energy Efficiency	Cost per month to run: (approx. \$1.50 for electricity to run fan, feed motor)	
Hopper Capacity	42 lbs.	26 lbs.			
Footprint	20" sq.	18.5" sq.			

Parlour T-4000 Wood Stove

A remarkable heater for size and shape, the Parlour T-4000 sets the standard for certified wood stoves. Clean burning 3.62 grams per hour is accomplished with secondary burn technology and air wash to assist cleaning the viewing glass. The firebox will hold several 16" hardwood or high density logs and burn all night. Safe, efficient, and renewable, wood burning is the "green" choice.

SPECIFICATIONS

Height: 43" Foot Print: 20" sq.
Weight: 210lbs. Door Opening: 9"x12"
Diameter: 20" Flue Diameter: 6"
BTU's: 38,300

PERFORMANCE

Heating Capacity: 1200-1500 Sq. Ft.*
Log Length: 16"

**Heating Capacity depends upon environment, insulation and quality of fuel.*

MODEL COLORS - CLASSIC

Painted (Metallic Finish): Black, Blue, Moss Green, Brow, Honey Glow Brown
Painted (Matte Finish): Satin Black, Forrest Green, Golden-fire Brown
(Custom Painted Color Matching Available at Additional Charge)
Porcelain Enamel: Ebony Black, Ivory, Burgundy Red, Majolica Brown, Thelin Green, Cobalt Blue



Gnome and Parlour are available in porcelain enamel and painted finishes.

Parlour & Gnome Direct Vent Gas Heaters

Gas heating and classic styling, not normally considered at the same time. Thelin leads the way with cutting edge direct vent gas heaters approved for home, sleeping quarters, and manufactured home installation. Variable speed room air fans are standard and consider the optional thermostat for carefree operation. Available in Natural Gas or LPG.

SPECIFICATIONS	PARLOUR	GNOME
Height.....	45"	34"
Weight	180 lbs.	145 lbs.
Diameter.....	20"	17.5"
Exhaust Diameter.....	6.625"	6.625"
Footprint.....	20" sq.	18.5"

PERFORMANCE	PARLOUR	GNOME
BTU (Nat. Gas).....	31,000	22,000
BTU (Lp Gas).....	28,000	13,200
Heating Capacity	1200- 1800 sq. ft.	500-800 sq. ft.
Fan Type Vented Circulator	115 Volts, 1.5 Amps, 60 Hz.	

Fuel - Natural Gas or Propane
(*must be specified at time of order*)
Fan - 75 CFM - AC
Pipe Exit Outside Wall (from floor 71" O.C. / PARLOUR)
Pipe Exit Outside Wall (from floor 46" O.C. / GNOME)
Wall Thermostat - Optional (must be millivolt)
Simpson DuraVent, Metalbestos or Security Direct Vent Pipe



Echo Gas Direct Vent Heater

The Echo Gas DV heater is a traditional free standing stove that can be used as a primary home and/or space heater. Available in six colors and both painted and porcelain finishes, Echo Gas is the perfect complement to any home decor.

CLEARANCES

Cast Top to Sidewall 7"
Cast Top to Backwall 5"
Floor..... 0"

SPECIFICATIONS

Height 29" (736.6mm)
Weight 26.5" (673mm)
Depth..... 20" (508mm)
Weight..... 215# (97.5K)
BTU (Nat. Gas)..... 27,000 Max
BTU (LP Gas)..... 26,000 Max
Heating Capacity..... 1200-1400 sq. ft.
Fuel: Natural or LP Gas
Pipe Exit: From floor to center of pipe 23.5"



Pellet Heater Standard Features:

Push-button control with clean function.
DC Microprocessor Control Fuel Feed.
Electronic 110V Ignition
Long Life Venturi Styled Cast Iron Firepot.
Easy Access - Cleaning and Maintenance.



No Power - No Problem!

Gain freedom from power outages with Thelin's onboard power back up system. DC Drive technology allows for safe continuous battery operation. Using only 35 watts of power, Thelin Pellet Heaters could run for days with a properly sized battery.



Power Up With Solar!

Thelin's microprocessor control lets you harness the power of the sun so you can run completely off the grid! With small solar panels and battery system Thelin's low 35 watt operation makes for a simple solar solution. Less Electricity than a low-wattage bulb: Thelin Pellet Heaters are approximately 10 times more efficient than most other pellet stoves.



Gas Heater Features:

High Efficiency Direct Vent Design.
Venting Horizontal & Vertical.
Installation in front of Fireplace or on Hearth.
Simple Pilot Ignition - Back up Heat.
Optional Thermostat & Room Fan.